



XpressFill

Technology to Bottle Your Passion

XF4100H 4-Spout Hot Fill



Features

- ▶ Temperatures up to 90 °C
- ▶ Fill spouts operate independently
- ▶ Mesh sediment inline strainer
- ▶ Stainless steel front and adjustable tray
- ▶ Food-grade components in flow path
- ▶ Laminar-flow designed filler spouts
- ▶ Self-priming, quiet diaphragm pump

Options

- ▶ **Inert Gas Flush:** for use of nitrogen or similar gas in the bottling (\$400)
- ▶ **Variable Flow Rate Control Valves:** to precisely control flow rate (\$250)
- ▶ **Custom Filler Spouts:** needed for bottling unusual-sized bottles or types (\$90 per set)
- ▶ **Transfer Kit:** provides the perfect method of transferring your product from bulk container to filler and then bottles (Included)

Specifications

Capacity: (in bottles per hour)
450 for wine or similar viscosity (750 mL)
Weight: 24 lbs
Dimensions: 16" w x 17" h x 15.5" d

Power Requirements

115 VAC
1.5 Amps
50/60 Hz

www.xpressfill.com Email: sales@xpressfill.com

265 Prado Road, Suite 1 San Luis Obispo, CA 93401 Toll Free 844-361-2750